



"Reliable Digital Security Products Manufacturer"

SPECIFICATION

Model	PIX-PCXV/RHCB1631
<b>System</b>	
Main Processor	HI3531A
Operating System	Embedded LINUX
<b>Video</b>	
Input	Analog: 16*(TVI/AHD: 5MP; AHD/TVI/CVI: 4MP; AHD/TVI: 3MP; AHD/TVI/CVI: 1080P/720P; Analog: 960H) Analog+Network: 14*Analog+2*network(Max 8MP), 12*Analog+4*network(Max 8MP), 10*Analog+6*network(Max 8MP), 8*Analog+8*network(Max 8MP), 6*Analog+10*network(Max 8MP), 4*Analog+12*network(Max 8MP), 2*Analog+14*network(Max 8MP) Network: 32*network(Max 8MP)(Total incoming bandwidth ≤200M)
Input	16CH BNC
Signal Type	Analog/AHD/CVI/TVI/Network
Output	1 HD, 1 VGA, 1CVBS
<b>Audio</b>	
Input	2Channel, RCA
Two-way Audio	NO
Output	1 Channel, RCA
<b>Alarm</b>	
Sensor Input	NO
Output	NO
Motion Detection	16 Channel(max 32 Channel in pure network mode)
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail
<b>PTZ</b>	
Interface	RS485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
<b>Display</b>	
VGA	Resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz
HD Output	Resolution: 3840×2160/30Hz, 1920 × 1080P /60Hz, 1280 × 1024 /60Hz
Display Split	36 Channel/25 Channel/16 Channel/9 Channel/8 Channel/4 Channel / 1Channel
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
<b>Recording</b>	
Video Compression	H.264/H.264+
Audio Compression	G711u
Resolution	5MP(2592×1944),5MP_HALF(1296×1944),4MP(2560×1440),4MP_HALF(1280×1440),3MP(2048×1536),1080P(1920×1080),720P(1280×720),960H(P:960×576/N:960×480)
Video Quality	worst/worse/ordinary/well/best
Record Rate	Analog:PAL:5MP(2592×1944 16*6fps),5MP_HALF(1296×1944 16*10fps), 4MP(2560×1440 16*8fps),4MP_HALF(1280×1440 16*12fps),3MP(2048×1536 16*9fps),1080P(1920×1080 16*12fps),720P(1280×720 16*25fps), 960H(960×576 16*25fps) NTSC:5MP(2592×1944 16*6fps),5MP_HALF(1296×1944 16*10fps), 4MP(2560×1440 16*8fps),4MP_HALF(1280×1440 16*15fps),3MP(2048×1536 16*9fps),1080P(1920×1080 16*15fps),720P(1280×720 16*30fps), 960H(960×480 16*30fps) Pure IP:PAL:4k@18×25fps,5MP@20×25fps,4MP@28×25fps,3MP@28×25fps,1080P@32×25fps,960P@32×25fps,720P@32×25fps,D1@32×25fps NTSC: 4k@18×30fps,5MP@20×30fps,4MP@28×30fps,3MP@28×30fps,1080P@32×30fps, 960P@32×30fps, 720P@32×30fps, D1@32×30fps
Record Mode	Manual\Timer\Motion Detection
<b>Playback &amp; Backup</b>	
Decode Capability	4CH 5M@30fps
Sync Playback	Pure Analog: 16CH 5M@6fps,16CH 5MP_HALF@10fps, 16CH 4M@7fps, 16CH 4MP_HALF@12fps, 16CH 3M@9fps, 16CH 1080p@15fps Mix Mode: 2CH 5M@30fps, 2CH 4M@30fps, 3CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps Pure IPC: 2CH 4K@30fps, 4CH 5M@30fps, 4CH 4M@30fps, 5CH 3M@30fps, 9CH 1080P@30fps, 9CH 960P@30fps, 9CH 720P@30fps
Remote Playback	4 Channel / 1 Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Rewind, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32 )/Network
<b>Network</b>	
Interface	1 RJ45 10M/100/1000M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF(1~25fps)
Smart Phone	iPhone, ipad, Android ,Android pad
<b>Hard Disk Driver</b>	
Interface Type	2 SATA Interface
Capacity	2 SATA Hard Disk (2.5"/3.5" SATA, Up to 12TB)
<b>General</b>	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V ≤10W (Without Hard Disk)
Working Environment	-10~55°C/10~90%
Dimension (W×D×H)	310*295*46(mm)
Weight	3.5kg (Without HDD)

PIXELS CONNECT PTE LTD

Address: 1013 GEYLANG EAST AVENUE 3, #01-172, SINGAPORE 389728

Tel: 6440 0023

E: sales@pixelsconnect.com.sg

W: www.pixelsconnect.com.sg