



"Reliable Digital Security Products Manufacturer"

SPECIFICATION

Model NO.	PIX-PCIPBB904XH800
<b>Camera</b>	
Image Sensor	1/2.5" SONY Starvis Back-illuminated CMOS Sensor
Resolution	8MP
Effective Pixels	3864(H)*2218(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Support, Internal
<b>Lens</b>	
Focus Length	3.3-12mm Motor Zoom
Focus Control	Auto
Lens Type	Auto
Pixels	4K
<b>Night Vision</b>	
Infrared LED	42μ x 6PCS
Infrared Distance	60M
IR Status	Auto Control
IR Power On	Auto Control
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	3840*2160 @15fps 3072*2048@30fps
Main Stream 2	2592*1944@30fps 2560*1920@30fps
Main Stream 3	2560*1440@30fps 1920*1080@30fps
Sub Stream 1	720*480@15fps 720*480@30fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@15fps 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
<b>Camera Features</b>	
Day/Night	Color/ B&W (IR-CUT )
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Full Starlight	/
Corridor Pattern	/
Defog Mode	Support
ROI	/
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands
<b>Interface</b>	
Audio	Optional
Alarm	/
SD Card Slot	Yes, Support Max 128GB
RS485	/
<b>General</b>	
Housing	IP66
Anti-cut Bracket	NO
IR Cut Filter	Yes, Support Max 128GB
Operation Temperature	-20℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 1150mA
Dimension	220(W) x 105(H) x 109(D)mm
Weight	1.4kgs

PIXELS CONNECT PTE LTD

Address: 1013 GEYLANG EAST AVENUE 3, #01-172, SINGAPORE 389728

Tel: 6440 0023

E: sales@pixelsconnect.com.sg

W: www.pixelsconnect.com.sg