



"Reliable Digital Security Products Manufacturer"

SPECIFICATION

Model NO.	PIX-PCIPBB905XH200	PIX-PCIPBB905XH200	PIX-PCIPBB905XH200
Camera			
Image Sensor	IMX323	IMX307	IMX327
Main processor	Hi3516C	Hi3516C	Hi3516C
Resolution	2MP 1080P	2MP 1080P	2MP 1080P
Effective Pixels	1985(H)*1105(V)	1945(H)*1097(V)	1945(H)*1097(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG		
TV System	PAL/NTSC		
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec		
S/N Ratio	≥52dB		
Scanning System	Progressive		
Video Output	Network		
Reset Button	Optional		
Lens			
Focus Length	2.7-13.5mm	2.7-13.5mm	2.7-13.5mm
Focus Control	Auto	Auto	Auto
Lens Type	Motorized	Motorized	Motorized
Pixels	5M	5M	5M
Night Vision			
Infrared LED	42μ x 6PCS		
Infrared Distance	60M		
IR Status	Auto Control		
IR Power On	Auto Control		
Network			
Ethernet	RJ-45 (10/100Base-T)		
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP		
ONVIF	Support ONVIF 2.4		
P2P	YES, Support QR Code		
POE	Optional, Support IEEE 802.3af		
Video Delay	0.3S (Within the Lan)		
Main Stream 1	2048*1536@15fps	2048*1536@15fps	2048*1536@15fps
Main Stream 2	1920*1080@30fps	1920*1080@30fps	1920*1080@30fps
Main Stream 3	1280*720@30fps	1280*720@30fps	1280*720@30fps
Sub Stream 1	720*480@15fps 720*480@30fps	720*480@15fps 720*480@30fps	720*480@15fps 720*480@30fps
Sub Stream 2	/	/	/
Sub Stream 3	/	/	/
Tri Stream	352*288@15fps 352*288@30fps	352*288@15fps 352*288@30fps	352*288@15fps 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari		
Smart Phone	iPhone, iPad, Android, Android Pad		
Camera Features			
Day/Night	Color/ B&W (IR-CUT)		
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)		
Full Starlight	/	/	/
Corridor Pattern	Support	Support	Support
Defog Mode	Support	Support	Support
ROI	Support	Support	Support
BLC	Support	Support	Support
HDR	/	/	/
WDR	Support	Support	Support
Motion Detection	Support	Support	Support
Privacy Masking	3 Rectangular Zone	3 Rectangular Zone	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web	NVR/NAS/CMS/Web	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands		
Interface			
Audio	Optional	Optional	Optional
Alarm	/	/	/
SD Card Slot	Optional, Support Max 128GB	Optional, Support Max 128GB	Optional, Support Max 128GB
RS485	/	/	/
General			
Housing	IP66		
Anti-cut Bracket	NO		
IR Cut Filter	YES		
Operation Temperature	-20℃ ~ +60℃ RH95% Max		
Storage Temperature	-20℃ ~ +60℃ RH95% Max		
Power Source	DC12V±10%,1150mA		
Dimension	220(W) x 105(H) x 109(D)mm		
Weight	1.4kgs		

PIXELS CONNECT PTE LTD

Address: 1013 GEYLANG EAST AVENUE 3, #01-172, SINGAPORE 389728

Tel: 6440 0023

E: sales@pixelsconnect.com.sg

W: www.pixelsconnect.com.sg