



PIXELS CONNECT PTE LTD




◆ SPECIFICATION

Model	PIX-PCCK-L9364PN
System	
Main Processor	ARM Cortex A17 Quad-core Processor
Operating System	Embedded LINUX
Video	
Input	64CH(4000×3000, 3840×2160, 2592×1944, 2048×1536, 1920×1080, 1280×960, 1280×720, etc)
Output	1 VGA, 2 HD
Audio	
Input	1 Port RCA
Output	1 Port RCA(Linear, 1kΩ)
Audio Bit Rate	64kbps
Audio Compression standard	AAC,G711u, G711a, ADPCM_DVI4
Intercom	support (two-way)
Alarm	
Sensor Input	16
Output	4
Motion Detection	64 Channel, MD Zones: 396 (22 × 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, alarm output
Display	
HD Output1	4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
HD Output2	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
VGA	1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
Display Split	64CHxD1/36CHxD1/25CHxD1/16CHxD1/9CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP/1CHx4k/1CHx12MP
Digital Zoom	YES
OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm
Recording	
Video Compression	H265/H264/H265+/H264+
Resolution	12MP(4000×3000),4k(3840×2160),5MP(2592×1944),4MP(2688×1520/2560×1440), 3MP(2048×1536),1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (720×576/720×480)
Record Rate	PAL:12MP@29×25fp,4k@35×25fp,5MP@58×25fp,4MP@64×25fp,3MP@64×25fp,1080P@64×25fp, 960P@64×25fp,720P@64×25fp, D1@64×25fp NTSC:12MP@29×30fp,4k@35×30fp,5MP@58×30fp,4MP@64×30fp,3MP@64×30fp,1080P@64×30fp, 960P@64×30fp, 720P@64×30fp, D1@64×30fp
Record Mode	Manual\Timer\Motion Detection\Alarm Input\Smart Event

Playback & Backup	
Local Sync Playback	3CH 12MP@15fps, 4CH 4K@30fps, 6CH 5MP@30fps, 8CH 4MP@30fps, 10CH 3M@30fps, 16CH 1080P@30fps, 16CH 960P@30fps, 16CH 720P@30fps,16CH D1@30fps
Decode Capability	4CH 4K(3840x2160)@30fps
Remote Sync Playback	YES
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection,Event Alarm,Tag search
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play ,Frame Rewind, Digital Zoom,tag,clip
Backup Mode	USB Device/Network
Network	
Interface	2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
Incoming Bandwidth	300MB
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTP, p2p,PPPOE
Onvif	onvif S,onvif T
Web Browser	Edge,IE8-11, Google Chrome , Firefox ,Safari
CMS Software	Support Windows 7/ Windows 8/Windows 10/MAC OS
Cloud Support	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
POE	/
WIFI UI	/
Storage	
Interface Type	8 SATA Hard Disk Interface (3.5" SATA)
Capacity	Up to 48TB capacity
eSATA	1 eSATA interface
General	
Language	Traditional Chinese, Simplified Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek, Vietnamese
USB Interface	2 USB 2.0 Interfaces ,1 USB 3.0 Interface
RS485	2 Port
Power Supply	AC 115 to230V,3A
Working Environment	-10~55 °C /10~90%
Dimension(WxDxH)	2U, 440mmx450mmx95mm
Weight	9.8Kg (without HDD)

Made In Taiwan



CCTV
Analog Camera, IP Camera
Dome & Bullet Cameras
Hidden Cameras
4K Cameras
PTZ Cameras



Wireless Cameras
Panoramic Camera
4K Action Camera | Car Cameras
Battery Cameras
WiFi Door Bells
Hidden Cameras



Biometric Devices
Fingerprint | Face | Card |
Access PIN Reader
Electromagnetic Lock
Exit Button | Break Glass
Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023