




PIXELS CONNECT PTE LTD



◆ SPECIFICATION

Model NO.	PIX-PCS300GS	PIX-PCS300GD
Basic Parameters		
Driver Signal	12V	
Driver Voltage	24V	
Movement	Single	Dual
Passing Speed	35 Persons/Min	
Traffic	Unidirectional/Bidirectional	
OPen & Close Time	0.5-1s	
Material	304 Stainless	
Channel Width	≤600mm	
Swing Arm	270mm/acrylic	
Card Reader	Support	
Counting People	Optional	
Illegal infiltration	Support	
Anti-pinch	Infrared/Mechanical	
Infrared	3 Pairs	
Interface		
RS485	RS485 electrical standard, communication distance: <1200 meters	
Input Port	Switch Signal(NO NC COM)	
Network Port	Optional	
General Specification		
Power	220V±10% 50Hz 110V±10% 60Hz(optional)	
Working Temperature	-30℃~60℃/10~95%	
Device Size	1200*300*980mm	
Package Size	126*68*116	126*98*116
Package Weight	257.4KGs	371.8KGs

Made In Taiwan



CCTV

Analog Camera, IP Camera
Dome & Bullet Cameras
Hidden Cameras
4K Cameras
PTZ Cameras



Wireless Cameras

Panoramic Camera
4K Action Camera | Car Cameras
Battery Cameras
WiFi Door Bells
Hidden Cameras



Biometric Devices

Fingerprint | Face | Card |
Access PIN Reader
Electromagnetic Lock
Exit Button | Break Glass
Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023