



PIXELS CONNECT PTE LTD



◆ SPECIFICATION


Model NO.	PIX-PCWIFICEB8218KE200
Package	
NVR	1x NVRCE8218KTW
Camera	8 x IPR25KE200W
WIFI Range	No Obstacles 300m Max
Cable	1 x 1m Net Cable
Mouse	1xUSB 2.0 Mouse
Adaptor	1xDC 12V 2A for WIFI NVR, 8xDC 12V 0.5A for WIFI IP Camera
Weight	5.3kg/SET
Camera Model	PIX-PCIPR25KE200W
Camera	
Image Sensor	1/2.9" Full HD CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1920(H)*1080(V)
Compression	H.264/H.264+/H.265/H.265+
TV System	PAL(default)
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Wireless network
Reset Button	Yes
LENS Type	
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	2M Pixels

Night Vision	
Infrared LED	14μ x 20PCS
Infrared Distance	25M
IR Status	Auto Control
IR Power On	Auto Control
Network	
Ethernet	/
Protocol	TCP/IP,ICMP,RTP,RTSP,RTCP
ONVIF	/
P2P	/
POE	/
Main Stream 1	1920*1080@1-15fps(default resolution:1920*1080/frame rate:15fps/bit rate:1Mbps)
Main Stream 2	/
Main Stream 3	/
Sub Stream 1	720*480@1-15fps(default frame rate:15fps/bit rate:0.5Mbps)
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	/
IE Brower	/
Smart Phone	/
Wireless	
Antena	3dbi
Hotspot	NO
Wi-Fi	Wi-Fi(IEEE802.11b/g/n)
WIFI Range	No obstacles 300m Max.
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, White Balance, FLK(Flicker Control)
Corridor Pattern	/
ROI	/
Defog Mode	/
BLC	/
HDR	/
WDR	/
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR
Language	/

Interface	
Audio	/
Alarm	/
SD Card Slot	/
RS485	/
General	
Housing	Metal , IP67
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-10℃ ~ +50℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	157(W) x 70(H) x 66(D)mm
Weight	650g
Model	PIX-PCNVRCE821W
System	
Main Processor	ARM Cortex A7 Quad-core Processor
Operating System	Embedded LINUX
Video	
Input	9CH (3840x2160,2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, etc)
Output	1 VGA, 1 HD
Audio	
Input	/
Output	1*3.5mm audio interface
Audio Bit Rate	64kbps
Audio Compression standard	G711u, G711a
Alarm	
Sensor Input	NO
Output	NO
Motion Detection	9 Channel, MD Zones: 396 (22 × 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips
Display	
HD1	Resolution: 4K(3840x2160)/30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
HD2	/
VGA	Resolution:1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Display Split	9CHxD1/8CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP/1CHx4K
Digital Zoom	YES
OSD	Camera Title, Time, Recording, Motion Detection, Alarm

Recording	
Video Compression	H.264/H.265/H.264+/H.265+
Resolution	4K(3840x2160),25MP(2592x1944),4MP(2688x1520),3MP(2048x1536), 1080P(1920x1080),960P(1280x960),720P(1280x720),D1 (720x576/720x480)
Record Rate	PAL :4K@8x25fps,5MP@9x25fp,4MP@9x25fp,3MP@9x25fp,1080P@9x25fp, 960P@9x25fp,720P@9x25fp, D1@9x25fp NTSC: 4K@8x30fps,5MP@9x30fp,4MP@9x30fp,3MP@9x30fp,1080P@9x30fp, 960P@9x30fp, 720P@9x30fp, D1@9x30fp
Record Mode	Manual\Timer\Motion Detection
Playback & Backup	
Local Sync Playback	1CH 4K@30fps,1CH 5MP@30fps, 1CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps,9CH D1@30fps
Decode Capability	4CH 1080P@30fps
Remote Sync Playback	YES
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play ,Frame Rewind, Digital Zoom
Backup Mode	Network/USB2.0
Network	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Incoming Bandwidth	Wired 80Mbps; wireless 28Mbps
Network Functions	TCP/CP, HTTP, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTP, RTSP, RTCP, p2p
Onvif Version	Support Onvif 2.4
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10
Cloud Support(P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android Pad
POE	/
WIFI	Support, WIFI Range: No Obstacles 300m Max.
Storage	
Interface Type	1 SATA Hard Disk Interface (2.5"/3.5" SATA)
Capacity	Up to 8TB capacity
eSATA	/
General	
Language	Traditional Chinese, Simplified Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek, Vietnamese,Japanese
USB Interface	2 USB 2.0 Interfaces
RS485	/
Power Supply	DC12V/2A
Working Environment	-10~55 °C/10~90%
Dimension(WxDxH)	219*217*40(mm)
Weight	2.0KG (without HDD)

Made In Taiwan



CCTV
Analog Camera, IP Camera
Dome & Bullet Cameras
Hidden Cameras
4K Cameras
PTZ Cameras



**Wireless
Cameras**
Panoramic Camera
4K Action Camera | Car Cameras
Battery Cameras
WiFi Door Bells
Hidden Cameras



**Biometric
Devices**
Fingerprint | Face | Card |
Access PIN Reader
Electromagnetic Lock
Exit Button | Break Glass
Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023