



PIXELS CONNECT PTE LTD



◆ SPECIFICATION

|                           |                            |
|---------------------------|----------------------------|
| Model NO.                 | PIX-PCAC71                 |
| <b>Package</b>            |                            |
| Camera                    | 1pcs                       |
| Adaptor                   | 1xDC 5V 1A                 |
| <b>Camera</b>             |                            |
| Image Sensor              | 1/2.9"CMOS sensor          |
| Resolution                | 3MP                        |
| Effective Pixels          | 2304(H)*1296(V)            |
| Compression               | H.265                      |
| Electronic Shutter Time   | Auto (1 / 12s~1 / 100000s) |
| S/N Ratio                 | 40dB                       |
| Scanning System           | Progressive                |
| Video Output              | Wireless network           |
| Reset Button              | Yes                        |
| <b>PTZ</b>                |                            |
| Horizontal Rotation Range | 0~355°                     |
| Tilt Rotation Range       | 0~60°                      |
| <b>LENS Type</b>          |                            |
| Focus Length              | 3.6mm F2.0                 |
| Focus Control             | Fixed                      |
| Lens Type                 | Fixed                      |
| Pixels                    | 3M Pixels                  |

| <b>Night Vision</b>    |                                   |
|------------------------|-----------------------------------|
| Infrared LED           | 14μ x 4PCS                        |
| Infrared Distance      | 5~10M                             |
| IR Status              | CDS Auto Control                  |
| IR Power On            | Auto Control                      |
| <b>Network</b>         |                                   |
| Ethernet               | RJ-45 (10/100Base-T)              |
| Protocol               | TCP/IP、UDP、HTTP、DDNS、DHCP、FTP、NTP |
| ONVIF                  | /                                 |
| P2P                    | Support                           |
| POE                    | /                                 |
| Main Stream 1          | 2304*1296@20fps                   |
| Main Stream 2          | /                                 |
| Main Stream 3          | /                                 |
| Sub Stream 1           | 640*360@20fps                     |
| Sub Stream 2           | /                                 |
| Sub Stream 3           | /                                 |
| Tri Stream             | /                                 |
| IE Brower              | /                                 |
| Smart Phone            | support                           |
| <b>Wireless</b>        |                                   |
| Antenna                | 3dbi                              |
| Hotspot                | Support                           |
| Wi-Fi                  | Wi-Fi(IEEE802.11b/g/n)            |
| WIFI Range             | No obstacles 350m Max.            |
| <b>Camera Features</b> |                                   |
| Day/Night              | Color/ B&W (IR-CUT )              |
| Minimum Illumination   | 0.01 Lux                          |
| Image Config           | YES                               |
| Corridor Pattern       | /                                 |
| ROI                    | /                                 |
| Defog Mode             | /                                 |

|                       |                         |
|-----------------------|-------------------------|
| BLC                   | /                       |
| HDR                   | /                       |
| 3DNR                  | Support                 |
| DWDR                  | Support                 |
| Motion Detection      | Support                 |
| Privacy Masking       | /                       |
| Recording Mode        | SDcard                  |
| Language              | Chinese、English         |
| <b>Interface</b>      |                         |
| Audio                 | 2-Way Audio             |
| Alarm                 | Motion Detection        |
| SD Card Slot          | Support Max 128G        |
| <b>General</b>        |                         |
| Housing               | plastic                 |
| Bracket               | Support                 |
| IR Cut Filter         | YES                     |
| Operation Temperature | -10°C ~ +50°C RH75% Max |
| Storage Temperature   | -20°C ~ +60°C RH75% Max |
| Size                  | 90(W)x155(H)x88(D)mm    |

Made in Taiwan



**CCTV**

Analog Camera, IP Camera  
Dome & Bullet Cameras  
Hidden Cameras  
4K Cameras  
PTZ Cameras



**Wireless  
Cameras**

Panoramic Camera  
4K Action Camera | Car Cameras  
Battery Cameras  
WiFi Door Bells  
Hidden Cameras



**Biometric  
Devices**

Fingerprint | Face | Card |  
Access PIN Reader  
Electromagnetic Lock  
Exit Button | Break Glass  
Video Door Intercom



**PIXELS CONNECT PTE LTD**

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023