


Split/Integrated Sensor PIX-PCAS-01

- * Split and integrated optional
- UART and USB communication optional
- User capacity: 1,000
- ★ 500DPI optical sensor
- High speed fingerprint identification algorithm engine
- * Fingerprint template data read from /write to FLASH memory function
- dentify downloaded feature with captured fingerprint



PIX-PCAS-01 is based on optical sensing technology which efficiently recognizes fingerprints at high speed, it can be flexibly integrated with various system applications.



Two types available: Split-type and Intergrated-type

UART and USB communication optional







Good Choice for Safe Lock

A good-looking guard to protect your important things

Integrated in Fingerprint Enrollment Device





Integrated in Fingerprint Device


Can be integrated in Fingerprint access control, fingerprint time attendance, fingerprint lock and so on



Fingerprint Capacity	1,000
Operating Voltage	5V DC
Idle Current	60mA
Active Current	80mA
Fingerprint Sensor	Optical Sensor
Resolution	500DPI
Identification time	< 1S
FAR	< 0.001% (Security Level 3)
FRR	< 0.005% (Security Level 3)
Communication Interface	UART or USB2.0/USB1.1
UART	9600 x N bps N=1~12 (Factory default N= 6 (38400bps)
Security Level	5 Levels (Level 1 is the lowest, Level 5 is the highest)
Matching Mode	1: N
Fingerprint Template	512 Bytes
Operating Temperature	-30°C~+70°C
Storage Temperature	-40 °C~+80 °C
Storage Humidity	15%RH~95%RH
Physical	ABS
Dimensions	20.9*17.3mm
Unit Weight	0.03Kg
Shipping Weight	0.05Kg



Product Size







Analog Camera, IP Camera Dome & Bullet Cameras Hidden Cameras 4K Cameras PTZ Cameras



Panoramic Camera 4K Action Camera | Car Camera Battery Cameras WiFi Door Bells Hidden Cameras



Fingerprint | Face | Card | Access PIN Reader Electromagnetic Lock Exit Button | Break Glass Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728 pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023