



## PIXELS CONNECT PTE LTD



### ◆ SPECIFICATION

Model	PIX-PCHT1612	
Power	Power Adapter Voltage	Input 100-240V/AC 50/60Hz
	The maximum power supply machine	240W
Protection level	Mould	+4KV
	Differential mode	+1KV
Network Connector	Network Port	1~16 port: :10/100Mbps PoE Ethernet port WAN1/WAN2 port:10/100/1000Mbps
	Transmission Distance	Extend switch is default OFF, state(1~16 port): 100m Extend switch is ON, state:(1~16 port:): 250m WAN1/WAN2 port: 100m
	Transmission Medium	Cat5/5e/6 standard network cable
Network Switch	Network Standard	IEEE802.3/10BASE-T
		IEEE802.3u/100BASE-TX
		IEEE802.3x Flow Control, IEEE802.3az
	Maximum Frame Size	1536 Bytes
	MAC address list	2K
	Backplane bandwidth	1Gbps
Power Over Ethernet	PoE Standard	IEEE802.3af/at
	PoE Power Supply Type	End-Span(4/5+;7/8-)
	PoE Power Consumption	af,at Adaptive (every port)
LED Status Indicator	POE Ethernet	When the PoE is powered, 1-16 LEDs are green
		When accessing Ethernet, ports 1-16 are yellow
Environmental	Working temperature	0°C~55°C
	Working humidity	10%-90% non-condensing
	Storage temperature	-40°C~70°C
	Storage Humidity	5%-95% RH non-condensing
Mechanical	Dimension (L x W x H) mm	290*200*44
	Material	SECC
	Color	Dark gray
Stability	MTBF	>30000h

Made in Taiwan



Analog Camera, IP Camera  
Dome & Bullet Cameras  
Hidden Cameras  
4K Cameras  
PTZ Cameras



Panoramic Camera  
4K Action Camera | Car Cameras  
Battery Cameras  
WiFi Door Bells  
Hidden Cameras



Fingerprint | Face | Card |  
Access PIN Reader  
Electromagnetic Lock  
Exit Button | Break Glass  
Video Door Intercom



## PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023