



PIXELS CONNECT PTE LTD



◆ SPECIFICATION

Model		
Power	Power Adapter Voltage	Input: 110-220V/AC 50-60Hz 5
	The maximum power supply machine	120W
Protection level	Mould	+4KV
	Differential mode	+1KV
Network Connector	Network Port	1~8 port: :10/100Mbps PoE Ethernet LAN port WAN port : 10/100Mbps Ethernet WAN port
	Transmission Distance	Extend switch is default OFF, state(1~8 port): 100m Extend switch is ON, state:(1~8 port.): 200m WAN port: 100m
	Transmission Medium	Cat5/5e/6 standard network cable
Network Switch	Network Standard	IEEE802.3/10BASE-T
		IEEE802.3u/100BASE-TX
		IEEE802.3x Flow Control, IEEE802.3az
	Maximum Frame Size	1536 Bytes
	MAC address list	2K
	Backplane bandwidth	1Gbps
Power Over Ethernet	PoE Power Supply Type	End-Span(4/5+;7/8-)
	PoE Power Consumption	af,at Adaptive (every port)
LED Status Indicator	PoE Ethernet	When the PoE is powered, 1-8 LEDs are green
		When accessing Ethernet, ports 1-8 are yellow
Environmental	Working temperature	0°C~55°C
	Storage temperature	-40°C~70°C
	Working humidity	10%-90% non-condensing
	Storage humidity	5%-95% non-condensing
Mechanical	Dimension (L x W x H) mm	220*140*40
	Material	SECC
	Color	Dark grey
Stability	MTBF	>30000h

Made in Taiwan



CCTV

Analog Camera, IP Camera
Dome & Bullet Cameras
Hidden Cameras
4K Cameras
PTZ Cameras



Wireless
Cameras

Panoramic Camera
4K Action Camera | Car Cameras
Battery Cameras
WiFi Door Bells
Hidden Cameras



Biometric
Devices

Fingerprint | Face | Card |
Access PIN Reader
Electromagnetic Lock
Exit Button | Break Glass
Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023