



PIXELS CONNECT PTE LTD



◆ SPECIFICATION

Model NO.	PIX-PCKLBAHD4005XESL	PIX-PCKLBATE4005XSH
Video Output Mode	EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps; AHD/TVI: 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 4M/2M@30fps/25fps;	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps; EX-SDI: 4M/2M@30fps/25fps. 2M@60fps/50fps, 2M@30fps/25fps, 720P@60fps/50fps, 720P@30fps/25fps; HD-SDI: 2M@30fps/25fps, 720P@30fps/25fps

Camera

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC	PAL/NTSC
Electronic Shutter	Auto	Auto
Scanning System	Progressive Scan	Progressive Scan

Lens

Focus Length	2.7-13.5mm Motor Zoom	2.7-13.5mm Motor Zoom
Focus Control	Auto	Auto
Lens Type	Auto	Auto

Night Vision

IR Cut Filter	YES	YES
Infrared LED	42μ x6PCS	42μ x6PCS
Infrared Distance	60M	60M
IR Status	AGC Auto Control	AGC Auto Control


Camera Features

Starlight	/	YES
Day/Night	YES	YES
OSD Menu	YES	YES
WDR	YES	YES
UTC	YES	YES
Noise Reduction	3DNR	3DNR
White Balance	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO

General

Housing	IP67	IP67
Bracket	YES	YES
Operation Temperature	-10°C ~ +60°C RH95% Max	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%,900mA	DC12V±10%,900mA
Dimension	313(W) x 109(H) x 106(D)mm	313(W) x 109(H) x 106(D)mm
Weight	2.15Kgs	2.15Kgs

Made in Taiwan



Analog Camera, IP Camera
Dome & Bullet Cameras
Hidden Cameras
4K Cameras
PTZ Cameras



Panoramic Camera
4K Action Camera | Car Cameras
Battery Cameras
WiFi Door Bells
Hidden Cameras



Fingerprint | Face | Card |
Access PIN Reader
Electromagnetic Lock
Exit Button | Break Glass
Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023