



PIXELS CONNECT PTE LTD



◆ SPECIFICATION

Model NO.	PIX-PCKSBCHTC800ESLW	PIX-PCKSBCHTC800FKEW
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps;	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; TVI/CVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps 4M/2M@30fps/25fps
<b>Camera</b>		
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor	1/2.5" CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC	PAL/NTSC
Electronic Shutter	Auto	Auto
Scanning System	Progressive Scan	Progressive Scan
<b>Lens</b>		
Focus Length	Board Lens 3.6mm	Board Lens 3.6mm
Focus Control	Fixed	Fixed
Lens Type	Fixed	Fixed
<b>Night Vision</b>		
IR Cut Filter	YES	YES
Infrared LED	No,Support Warm light LED 3030*2	No,Support Warm light LED 3030*2
Light Distance	up to 25M	up to 25M
IR Status	AGC Auto Control	AGC Auto Control
<b>Camera Features</b>		
Starlight	/	/
Day/Night	Color	Color
OSD Menu	YES	YES
WDR	YES	DWDR
UTC	YES	YES
Noise Reduction	3DNR	DNR
Coaxial Audio	/	YES(only TVI )
White Balance	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO
<b>General</b>		
Housing	IP67	IP67
Bracket	YES	YES
Operation Temperature	-10°C ~ +60°C RH95% Max	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%,700mA	DC12V±10%,700mA
Dimension	169.5L*70 W*67.5	169.5L*70 W*67.5
Weight	600g	600g



Analog Camera, IP Camera, Dome & Bullet Cameras, Hidden Cameras, 4K Cameras, PTZ Cameras



Panoramic Camera, 4K Action Camera | Car Cameras, Battery Cameras, WiFi Door Bells, Hidden Cameras



Fingerprint | Face | Card | Access PIN Reader, Electromagnetic Lock, Exit Button | Break Glass, Video Door Intercom

Made in Taiwan



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023