

## PIXELS CONNECT PTE LTD



## ♦ SPECIFICATION

Model NO.	PIX-PCKSCAHT800ESLW	PIX-PCKSCAHTC800FKEW
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps;	AHO: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; TVI/CVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps 4M/2M@30fps/25fps
Camera		
Image Sensor	1/2.8" SONY Starvis Back- illuminated CMOS sensor	1/2.5" CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC	PAL/NTSC
Electronic Shutter	Auto	Auto
Scanning System	Progressive Scan	Progressive Scan
Lens		
Focus Length	Board Lens 3.6mm	Board Lens 3.6mm
Focus Control	Fixed	Fixed
Lens Type	Fixed	Fixed
Night Vision		
IR Cut Filter	YES	YES
Infrared LED	No,Support Warm light LED double3015U×2	No,Support Warm light LED double3015U×2
Light Distance	up to 25m	up to 25m
IR Status	AGC Auto Control	AGC Auto Control
Camera Features		
Starlight	1	1
Day/Night	YES	Color
OSD Menu	YES	YES
WDR	YES	DWDR
итс	YES	YES
Noise Reduction	3DNR	DNR
Coaxial Audio	1	YES(only TVI )
White Balance	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO
General		
Housing	IP67	IP67
Bracket	NO	NO
Operation Temperature	-10°C ~ +60°C RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%,450mA	DC12V±10%,450mA
Dimension	⊄96 x 96*91 mm	⊄96 x 96*91 mm
Weight	600g	600g











Biometric Devices

