



# PIXELS CONNECT PTE LTD



### ◆ SPECIFICATION

Model NO.	PIX-PCPT5AM22XH500
<b>Camera</b>	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H265
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	45°/s
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	30°/s
Tilt Rotation Range	0°~93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
<b>Lens</b>	
Focus Length	3.9mm-85.5mm
Focus Control	22X Optical Zoom
<b>Night Vision</b>	
Infrared LED	☉ 42x6PCS
IR Range	120m
Day-night mode	AUTO
<b>Network</b>	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	2560*1920@20fps
Main Stream2	2560*1440@25fps
Main Stream3	2304*1296@25fps
Main Stream4	1920*1080@25fps
Main Stream5	1280*720@25fps
Main Stream6	640*512@25fps
Sub Stream1	800*448@25fps
Sub Stream2	704*576@25fps
Sub Stream3	640*360@25fps
Sub Stream4	352*288@25fps
<b>Interface</b>	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	Optional
<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V 2A/3A
Lightning Protection	Transient voltage 6000V
Dimension	29.5x28x17(cm)
Weight	4.2Kgs

Made in Taiwan



**CCTV**  
 Analog Camera, IP Camera  
 Dome & Bullet Cameras  
 Hidden Cameras  
 4K Cameras  
 PTZ Cameras



**Wireless  
Cameras**

Panoramic Camera  
 4K Action Camera | Car Cameras  
 Battery Cameras  
 WiFi Door Bells  
 Hidden Cameras



**Biometric  
Devices**

Fingerprint | Face | Card |  
 Access PIN Reader  
 Electromagnetic Lock  
 Exit Button | Break Glass  
 Video Door Intercom



## PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023