



PIXELS CONNECT PTE LTD



◆ SPECIFICATION

Model	PIX-PCRT2418		
Power	Power Adapter Voltage	Input 100-240V/AC 50/60Hz	
	The maximum power supply machine	370W	
Protection level	Mould	+4KV	
	Differential mode	+1KV	
Network Connector	Network Port	1~24 port: :10/100Mbps PoE Ethernet port 25~28 port:10/100/1000Mbps WAN1/WAN2 port	
	Transmission Distance	1~24 port: Recommended distance is 100m	
	Transmission Medium	Cat5/5e/6 standard network cable	
Network Switch	Network Standard	IEEE802.3/10BASE-T Ethernet	
		IEEE802.3u/100BASE-TX Ethernet	
		IEEE802.3ab 1000BASE-T Ethernet	
	Maximum Frame Size	1536 Bytes	
	MAC address list	2K	
Power Over Ethernet	PoE Standard	IEEE802.3af/at	
	PoE Power Supply Type	End-Span(4/5+;7/8-)	
LED Status Indicator	POE Ethernet	PoE Power Consumption	at, (every port)
		POE Ethernet	POE: 24 green light indicates that the POE is power on Ethernet: 24 yellow light indicates that the Ethernet Link and Act
Environmental	Working temperature	0°C~50°C	
	Working humidity	0%-90% non-condensing	
	Storage temperature	-40°C~85°C	
	Storage Humidity	0%-90% RH non-condensing	
Mechanical	Dimension (L x W x H) mm	441*300*44	
	Material	SECC	
	Color	Dark gray	
Stability	MTBF	>30000h	

Made in Taiwan



CCTV

Analog Camera, IP Camera
Dome & Bullet Cameras
Hidden Cameras
4K Cameras
PTZ Cameras



**Wireless
Cameras**

Panoramic Camera
4K Action Camera | Car Cameras
Battery Cameras
WiFi Door Bells
Hidden Cameras



**Biometric
Devices**

Fingerprint | Face | Card |
Access PIN Reader
Electromagnetic Lock
Exit Button | Break Glass
Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023