



PIXELS CONNECT PTE LTD

7/4 bytes Mifare Reader PIX-PCS3-R MF

- ❄️ Waterproof, conforms to IP66
- ❄️ Identifies UID 7 bytes / 4 bytes
- ❄️ Wiegand 34/56 bits or 34/58bits (default: 34/56 bits)
- ❄️ Card type: 13.56MHz Mifare card
- ❄️ Working temperature: -40°C ~ 60°C (-13°F ~ 140°F)
- ❄️ Reading range: 5 cm



34/56bits,34/58bits



UID 7byte / 4byte



Protection Rating

The PIX-PCS3-R MF is a contactless proximity card reader.
It identifies UID 7 bytes / 4 bytes of 13.56MHz Mifare cards/fobs.



Identifies UID 7byte / 4byte



PIXELS CONNECT PTE LTD

Wiegand 34/56 bits (Default)
Wiegand 34/58 bits (Optional)



Programmable wiegand format with an extra wire

Waterproof, conforms to IP66





PIXELS CONNECT PTE LTD

Operation Voltage	9~24V DC
Standby Current	≤50mA
Card Type	13.56MHz Mifare Cards/Fobs (ISO14443A compatible) (identifies UID 7bytes / 4 bytes)
Read Range	2~6cm
Output Format	34bits/56bits wiegand (default) 34bits/58bits (optional)
Index of Protection	IP66
Color	Black / Ivory
Operating Temperature	-40°C~+60°C
Operating Humidity	0%~98%
Dimension	H120*W48*T20
Net Weight	170g



CCTV

Analog Camera, IP Camera
Dome & Bullet Cameras
Hidden Cameras
4K Cameras
PTZ Cameras



Wireless Cameras

Panoramic Camera
4K Action Camera | Car Cameras
Battery Cameras
WiFi Door Bells
Hidden Cameras



Biometric Devices

Fingerprint | Face | Card |
Access PIN Reader
Electromagnetic Lock
Exit Button | Break Glass
Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023