



PIXELS CONNECT PTE LTD

Metal Wiegand Reader (E/H/MF) PIX-PCS9-RX

- * Metal Case, anti-vandal
- * Waterproof, conforms to IP66
- * Wiegand Format:
 - EM: 26 bits
 - Mifare: 34/58 bits (32/56 bits optional)
 - HID: 26 bits
- * Card type: Hid card, EM card & Mifare card (4 bytes or 7 bytes)
- * Reading range: 3~8cm
- * External LED Control & External Buzzer Control



The PIX-PCS9-RX reader is an advanced 125KHz & 13.56MHz technology proximity reader. Because of metal case anti-vandal and waterproof, it can be mounted either indoor or outdoor in harsh environment.

Read 125KHz EM / HID card,
13.56MHz Mifare cards





PIXELS CONNECT PTE LTD



Waterproof, conforms to IP66

Metal, anti-vandal



50cm cable
(Standard)



RJ45
(optional)



Terminal Blocks
(Optional)

3 Kinds of Interface



PIXELS CONNECT PTE LTD

Data 0

Data 1



EM: 26 bits

Mifare: wiegand 34 bits (4 bytes card format) or 58 bits (7 byts card format)

HID: Automatically Recognize

Operating Voltage	9~24V DC
Frequency	125KHz & 13.56MHz
Card Type	125KHz - EM & Hid Card 13.56MHz - Mifare Card (ISO 14443A Compatible) 4 bytes or 7 bytes
Reading Distance	3~8 CM
Output Format	EM: Wiegand 26 bits
	Mifare: Wiegand 34/58 bits (32/56 bits optional)
	HID: Wiegand 26 bits
Operating Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Standby Current	< 25mA
Operating Humidity	10%~98% RH
Index of Protection	IP66
Dimensions	L105 x W50 x H20 (mm)



CCTV

Analog Camera, IP Camera
Dome & Bullet Cameras
Hidden Cameras
4K Cameras
PTZ Cameras



Wireless Cameras

Panoramic Camera
4K Action Camera | Car Cameras
Battery Cameras
WiFi Door Bells
Hidden Cameras



Biometric Devices

Fingerprint | Face | Card |
Access PIN Reader
Electromagnetic Lock
Exit Button | Break Glass
Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023