




## PIXELS CONNECT PTE LTD

### Outdoor Keypad & Reader PIX-PCSK1-W

- \* Waterproof, conforms to IP66
- \* One relay, 1000 users (990 Normal Users + 10 Visitor Users)
- \* 3 access modes: Card, PIN, Card + PIN
- \* Card type: 125KHZ EM card/ 13.56MHz Mifare card
- \* PIN length: 4~6 digits
- \* Wiegand 26~37bits input & 26bits output
- \* Facility code programmable
- \* Latch mode to hold door or gate open
- \* Working Temperature: -40°C ~ 60 °C (-40 °F ~ 140 °F)



Protection Rating



Temperature Range



Anti-Vandal

The PIX-PCSK1-W is a single-entry Access Control with integrated keypad and card reader. It supports up to 1000 users in multiple access configurations(Card,PIN,or Card+PIN). The built in reader supports 125KHz EM cards or 13.56MHz Mifare cards with Wiegand 26~37bits input & 26bits output.



USER TYPE: CARD, PIN  
Card type:  
125KHz EM card  
13.56MHz Mifare card



PIXELS CONNECT PTE LTD

Backlit and LED status  
can be set (ON/OFF)



-40°C resistance  
IP66 waterproof

Wide Voltage Range:

**12~28**  
VOLTS VOLTS





**PIXELS CONNECT PTE LTD**


<b>User Capacity</b>	<b>1000 Card/PIN (990 Normal Users + 10 Visitor Users)</b>
<b>Operating Voltage</b> Idle Current Active Current	<b>12~28V AC/DC</b> 55mA 80mA
<b>Keypad</b> PIN length	<b>12 Key (3*4)</b> 4 ~ 6 digits
<b>Proximity Card Reader</b> Radio Technology Read Range	<b>EM/Mifare (Optional)</b> 125KHz EM/ 13.56MHz Mifare Card 3 ~ 6 cm
<b>Wiring Connections</b>	Electric lock, exit button, DOTL, external alarm, Wiegand (in/out)
<b>Relay</b> Adjustable Relay Output Time Adjustable Alarm Output Time Lock Output Load Alarm Output Load	<b>ONE (NO, NC, COM)</b> 0 ~ 99 Seconds (5 seconds default) 0 ~ 3 minutes (1 minute default) 3 Amp Maximum 3 Amp Maximum
<b>Wiegand Interface</b>	Wiegand 26 bit input/output
<b>Environment</b> Operating Temperature Operating Humidity	<b>Meets IP66</b> -40°C ~ 60 °C (-40 °F ~ 140 °F) 10% ~ 90% Non-Condensing
<b>Physical</b> Surface Finish Dimensions Unit Weight Shipping Weight	<b>Zinc-Alloy Enclosure</b> Powder Coat 11.7L x 7.6W x 2.5H (cm) 600g 700g

**Product Size**





PIXELS CONNECT PTE LTD



**CCTV**

Analog Camera, IP Camera  
Dome & Bullet Cameras  
Hidden Cameras  
4K Cameras  
PTZ Cameras



**Wireless  
Cameras**

Panoramic Camera  
4K Action Camera | Car Cameras  
Battery Cameras  
WiFi Door Bells  
Hidden Cameras



**Biometric  
Devices**

Fingerprint | Face | Card |  
Access PIN Reader  
Electromagnetic Lock  
Exit Button | Break Glass  
Video Door Intercom



**PIXELS CONNECT PTE LTD**

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023