

Outdoor Dual-relay Keypad PIX-PCSK4

* Waterproof, conforms to IP66

* Two relays operation

* 1,100 users (Card, PIN, Card + PIN)

* Card type: 125KHZ EM card

PIN length: 4~6 digits

Latch mode to hold door or gate open

★ Working Temperature: -40°C ~ 60°C (-40 °F ~ 140 °F)







The PIX-PCSK4 is a dual-entry Access Control with integrated keypad and card reader.It supports up to 1100 users in multiple access configurations(Card,PIN,or Card +PIN).Its built-in card reader supports EM 125KHz frequency cards.





Two relays for two doors



-40°C, Low temperature for harsh environment





IP66 Waterproof

Wide Voltage Range:

12 ~ 28 VOLTS VOLTS








User Capacity Zone 1 Zone 2	1100 Card/PIN 1000 100
Operating Voltage Idle Current Active Current	12~28V AC/DC 55mA 80mA
Keypad	12 Key (2*6)
Proximity Card Reader Radio Technology Read Range	EM 125KHz Industry Standard Proximity Card 3 ~ 6 cm
Wiring Connections	Electric lock, exit button, DOTL, external alarm, door bell
Relay Adjustable Relay Output Time Adjustable Alarm Output Time Lock Output Load Alarm Output Load	Two (NO, NC, COM) 0 ~ 99 Seconds (5 seconds default) 1 ~ 3 minutes (1 minute default) 3 Amp Maximum 3 Amp Maximum
Environment Operating Temperature Operating Humidity	Meets IP66 -40°C ~ 60 °C (-40 °F ~ 140 °F) 10% ~ 90% Non-Condensing
Physical Surface Finish Dimensions Unit Weight Shipping Weight	Zinc-Alloy Enclosure Powder Coat 13.0L x 5.6W x 2.3H (cm) 500g 650g

Product Size









Analog Camera, IP Camera Dome & Bullet Cameras Hidden Cameras 4K Cameras PTZ Cameras



Panoramic Camera 4K Action Camera | Car Cameras Battery Cameras WiFi Door Bells



Fingerprint | Face | Card | Access PIN Reader Electromagnetic Lock Exit Button | Break Glass Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728 pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023