



PIXELS CONNECT PTE LTD

### Middle Range UHF Reader PIX-PCSUHF-1

- ❄ Waterproof, IP65
- ❄ Free demo and SDK
- ❄ Stable reading distance: 1~5m
- ❄ Frequency: 902~928MHz or customize other frequency

The PIX-PCSUHF-1 is a middle reading range, waterproof access control Reader.



Stable reading distance: 1~5m





## PIXELS CONNECT PTE LTD



Waterproof, Working temperature: -40°C ~ +65°C



Support Protocol: ISO18000-6B  
or ISO18000-6C(EPC GEN2)  
communication interface: RS485,  
RS232,Wiegand26,Wiegand34,RJ45





Working Frequency	Nationalstandard(920~925MHz), America standard (902~928MHz),or customize other frequency
Support Protocol	ISO18000-6B,ISO18000-6C(EPC GEN2)
Frequency Hopping	FHSS or fixed frequency set by software
Working Way	automatically reading card at regular time,can set reading card way.
Frequency Power	0~30dBm,be adjusted by software
Reading Distance	1~5M
Reading Sensitivity	dual polarization reading



## PIXELS CONNECT PTE LTD

Reading Speed	one label 64 bit ID number < 6ms
Antenna	build-in circular polarization antenna, gain 8dB /build-in linear polarization antenna, gain 12dBi
Interface	RS485, RS232, Wiegand26, Wiegand34, RJ45
Working Voltage	DC+12V
Working Status Indication	buzzer
Power	1W
Working Temperature	-40°C ~ +65°C
Storage Temperature	-45°C ~ +95°C
Working Humidity	20% ~ 95%(no condensing)
Dimension	232mm× 232mm× 55mm

Product Size



### CCTV

Analog Camera, IP Camera  
Dome & Bullet Cameras  
Hidden Cameras  
4K Cameras  
PTZ Cameras



### Wireless Cameras

Panoramic Camera  
4K Action Camera | Car Cameras  
Battery Cameras  
WiFi Door Bells  
Hidden Cameras



### Biometric Devices

Fingerprint | Face | Card |  
Access PIN Reader  
Electromagnetic Lock  
Exit Button | Break Glass  
Video Door Intercom



## PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023