



PIXELS CONNECT PTE LTD

### Mini Control Board PIX-PCSboard-III

- ❄️ 999 users, user data can be transferred
- ❄️ Multi access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs
- ❄️ Can connect with any reader with Wiegand 26~44, 56, 58, 64 bits output
- ❄️ Can connect with any keypad reader with 4bits, 8bits (ASCII) output
- ❄️ 12~28V AC/DC power input, 12V DC output
- ❄️ Can connect with external alarm and door contact



12~28V AC/DC



External Alarm Interface



Wiegand  
26~44 56 58 64 bits

PIX-PCSboard-III is a mini size single door access control board, it supports 12~28V AC/DC power supply, Wiegand 26~44, 56, 58, 64 bits input, and it can work with external alarm.



Mini Size:91x20x48mm



PIXELS CONNECT PTE LTD

The alarm signal can be sent to external alarm hardware



User Capacity 999 users

Wide Voltage Range:

**12 ~ 28**  
VOLTS VOLTS





PIXELS CONNECT PTE LTD



User Capacity	999
Operating Voltage Idle Current	12~28V AC/DC < 20mA
Relay Adjustable Relay Output Time Lock Output Load	One (NO, NC, Common) 0~300 Seconds (5 seconds default) 2 Amp Maximum
Wiegand Interface Input	Wiegand 26~44, 56, 58, 64 bits
Environment Operating Humidity	Indoor 0 ~ 90%RH
Physical Colour Dimensions Unit Weight Shipping Weight	ABS Shell Black L91 x W48 x D20 (mm) 63g 73g



## PIXELS CONNECT PTE LTD

### Product Size



#### CCTV

Analog Camera, IP Camera  
Dome & Bullet Cameras  
Hidden Cameras  
4K Cameras  
PTZ Cameras



#### Wireless Cameras

Panoramic Camera  
4K Action Camera | Car Cameras  
Battery Cameras  
WiFi Door Bells  
Hidden Cameras



#### Biometric Devices

Fingerprint | Face | Card |  
Access PIN Reader  
Electromagnetic Lock  
Exit Button | Break Glass  
Video Door Intercom



## PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023