



PIXELS CONNECT PTE LTD

Electric Bolt (For Narrow Door) PIX-PCSLock 4

- * Fail safe: Locked when energized
- * Holding force: 800kg
- * Face plate size: 20.0L x 2.45W x 3.5H (cm)
- * Strike size: 9.0L x 2.5W x 0.2H (cm)
- * Operating voltage: DC12V
- * 12V DC Narrow Door Dead Bolt Lock / Electric Drop Lock NO/NC Type

01

METAL LOCK BODY

Aluminum alloy body, brushed aluminum alloy plate treatment, safe and stable, durable



02

TONGUE

The locking tongue adopt arc edge design. Once the lock is released, the tongue will not rebound. Cylinder strength: stainless steel polished, withstand 800kg pull

03

SMART BOARD

Prevents illegal insertion of magnetic segments and prevents external interference. Operating voltage: 12VDC \pm 10%. Working current: 80mA





PIXELS CONNECT PTE LTD



04 HEXAGON SEREW
 This section of the electric plug lock new upgradeHexagon screw.fixed panel durable, to give customers better protection

05 DELAY ADJUSTMENT
 New design concept, adjustable delay electric plug lock 0, 3, 6 seconds adjustable delay, simple and quick Feedback output: NO NC COM feedback output



06 ALL ACCESSORIES
 Electric BOLT locks, decorative cover plates, induction magnets, matching screws, all-metal construction, we are only doing ourbest to make customers more satisfied

Product Parameter	Parameter Description
Fail Safe	Locked when energized
Face Plate	20.0L x 2.45W x 3.5H (cm)
Strike	9.0L x 2.5W x 0.2H (cm)
Bolt	1.6cm DIA, stainless steel 1.6cm throw
Voltage	12V DC



PIXELS CONNECT PTE LTD


Start Current	900mA
Standby Current	80mA
Solid Bolt	Polishing housing, 800Kg holding force
Suitable For	Wooden door, glass door, metal door
Signal Output	Door status output, NC/COM
Surface Temp	Low Temperature
Induction Distance	8mm
Operating temp	-10 °C ~ 55 °C (14 °F ~ 131 °F)
Operating Humidity	0% ~ 90%(non-condensing)
Special Designed	Tested to 500000 cycles
Face place material	High aluminum, carrulous line finished
Weight	0.75kg

Product Size

Face Plate: 20.0L x 2.45W x 3.5H (cm)

Strike: 9.0L x 2.5W x 0.2H (cm)

Weight: 0.75kg



CCTV

Analog Camera, IP Camera
Dome & Bullet Cameras
Hidden Cameras
4K Cameras
PTZ Cameras



**Wireless
Cameras**

Panoramic Camera
4K Action Camera | Car Cameras
Battery Cameras
WiFi Door Bells
Hidden Cameras



**Biometric
Devices**

Fingerprint | Face | Card |
Access PIN Reader
Electromagnetic Lock
Exit Button | Break Glass
Video Door Intercom



PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023