



PIXELS CONNECT PTE LTD

## WiFi TouchKey Access Controller PIX-PCH3-WIFI

- \* Touch keypad
- \* Waterproof, conforms to IP66
- \* Metal housing, anti-vandal
- \* Card type: EM Card or Mifare Card
- \* iOS and Android available
- \* Add / Delete users by APP
- \* Can set Time Restriction for users
- \* Temporary Password (One-time Or Period Code)
- \* Support checking Opening Record
- \* Remotely Access (Support 3G/4G/5G)
- \* Multiple Access Modes: Smartphone, Card, PIN
- \* Doorbell Call Notice



The PIX-PCH3-WIFI is a WiFi waterproof touch keypad & RFID access controller. It's integrated with Tuya which supports 500 mobile users and 1000 common users (including card/ PIN users).It's available for both iOS and Android.




2.4G WiFi network,  
Mobile APP Access  
APP name:  
TuyaSmart or Smartlife





PIXELS CONNECT PTE LTD

User Management  
Super Admin or Admin can  
Add/Delete users in APP



Opening History

DoorBell Call Notice





PIXELS CONNECT PTE LTD



Remotely Open Anywhere  
Support 3G/4G/5G

Temporary Code -  
One-time or Period code  
can be programmable





PIXELS CONNECT PTE LTD



<b>User Capacity</b> Common User Visitor User Panic User	<b>Hardware User: 1000</b> <b>APP User: 500</b> 988 PIN/Card Users) 10 2
<b>PIN Length</b>	<b>4~6 digits</b>
<b>Operating Voltage</b> Idle Current Active Current	<b>12~18V DC</b> ≤ 60mA ≤ 150mA
<b>Proximity Card Reader</b> Radio Technology Read Range	<b>EM or Mifare</b> 125KHz/13.56MHz 2~6cm
<b>Wiring Connections</b>	<b>Relay output, exit button, alarm, door contact, Wiegand input/output</b>
<b>Relay</b> Adjustable Relay Output Time Lock Output Load	<b>One (NO, NC, Common)</b> 0~99 Seconds (5 seconds default) 2 Amp Maximum
<b>Wiegand Interface</b>  PIN Output	<b>EM card version: Wiegand 26~44 bits input &amp; output</b> (Factory default: Wiegand 26bits) <b>Mifare card version:Wiegand 26~44 bits,56bits,58bits input &amp; output</b> (Factory default: Wiegand 34bits) 4 bits,8bits (ASCII),10 digits Virtual Number(Factory default:4bits)
<b>Environment</b> Operating Temperature Operating Humidity	<b>Meets IP66</b> -40°C ~ 60°C (-40°F ~ 140°F) 0%RH ~ 98%RH



## PIXELS CONNECT PTE LTD

<b>Physical</b>	<b>Zinc-Alloy</b>
Color	Sliver & Black
Dimensions	L148 x W43.5 x H22 (mm)
Unit Weight	330g
Shipping Weight	405g

### Product Size



**CCTV**

Analog Camera, IP Camera  
Dome & Bullet Cameras  
Hidden Cameras  
4K Cameras  
PTZ Cameras



**Wireless  
Cameras**

Panoramic Camera  
4K Action Camera | Car Cameras  
Battery Cameras  
WiFi Door Bells  
Hidden Cameras



**Biometric  
Devices**

Fingerprint | Face | Card |  
Access PIN Reader  
Electromagnetic Lock  
Exit Button | Break Glass  
Video Door Intercom



### PIXELS CONNECT PTE LTD

1013, Geylang East Ave 3, #01-144 Singapore 389728

pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023