

IK10 Metal Wiegand Reader (E/H/MF) PIX-PCX2-RX

- 😤 IK10 anti collision
- 😤 Metal Case, anti-vandal
- 😤 Waterproof, conforms to IP66
- * Wiegand 26~44, 56, 58 bits output
- Card Type: 125KHz Hid & EM cards, 13.56MHz NXP Mifare, Mifare Plus, DesFire, Mifare Pro, Mifare UltraLight, Mifare Class 4K cards
- * Reading range: 2~6cm
- * External LED Control & External Buzzer Control









The PIX-PCX2-RX is an IK10 certified reader, it is powerful in card reading type, can read 125KHz Hid & EM cards, 13.56MHz Mifare cards at the same time. Because of metal case anti-vandal and waterproof, it can be mounted either indoor or outdoor in harsh environment.



Card Type 125KHz HID & EM cards, 13.56MHz NXP Mifare, Mifare Plus, DesFire, Mifare Pro, Mifare UltraLight, Mifare Class 4K cards





IP66 Waterproof



Equip with a remote control can set the Wiegand output from 26~44, 56, 58bits

-40°C Low working temperature





Operating Voltage	9~24V DC
Frequency	125KHz & 13.56MHz
Card Type	125KHz - EM & Hid Card 13.56MHz - NXP Mifare, Mifare Plus, DesFire, Mifare Pro, Mifare UltraLight, Mifare Class 4K cards
Reading Distance	2~6 CM
Output Format	Wiegand 26~44, 56, 58 bits
Operating Temperature	-40 °C ~ 60 °C (-40 °F ~ 140 °F)
Standby Current	< 25mA
Operating Humidity	10%~98% RH
Index of Protection	IK10 & IP66
Dimensions	L105 x W49 x H21 (mm)



Net Weight	240g
Shipping Weight	270g

Product Size





pixelsconnect@gmail.com | www.pixelsconnect.com.sg | Tel:+65 6440 0023

PIX-PCX2-RX (IK10 METAL WIEGAND READER (E/H/MF))

PIXELS CONNECT PTE. LTD.